



Assembly Instructions for Pendant Light:

- Carefully unpack and identify all parts referring to illustration for parts identification.
- Turn the power to the installation point OFF.
- Remove the hex nut (a), lock washer (b), flat washer (c) and canopy (d) from the top assembly (A). Place the canopy (d), flat washer (c) and lock washer (b) onto the loop (e), secure with hex nut (a).
- Unravel the supply power and ground wires and pass them through the center tube (D), glass panel (B), top assembly (A), stems (H), stem (I), loop (J) and canopy assembly (L).
- Thread the top assembly (A), the glass panel (B), the center tube (D) and the socket assembly (E) as shown. Tighten until snug.
- Thread the bottom of stem (H) to the top assembly (A). Repeat process for remaining stems (H) and stem (I). Hand tighten until snug. Install the loop (J) onto the top of stem (I).
- Use carabiner (K) to connect the loop (J) to the loop on the canopy assembly (L) and twist the locking mechanism to secure.
- Install proper bulbs (not included) into each socket referring to the markings and/or labels on the fixture for maximum wattage.
- Place the glass shade (F) over the base (G).
- Confirm that the holes on the top assembly (A) align with the mounting holes on the base (G). Pass the finial (C) through holes of the top assembly (A) and thread into the mounting holes on the base (G). Hand-tighten until snug.
- Refer to the additional installation instructions included with the product for wiring and installation.
- Restore power to the installation point and retain this sheet for future reference.